

Section 1 Chemical Product and Company Identification

Page E1 of E2



5100 West Henrietta Rd
PO Box 92912
Rochester, NY 14692-9012
Tel: (800) 962-2660

Boreal Science
399 Vansickle Road
St. Catharines, Ontario
L2S 3T4 Canada
Tel: (800) 387-9393

CHEMTREC 24 Hour Emergency USA
Phone Number (800) 424-9300
For laboratory and industrial use only.
Not for drug, food or household use.

Product	GRAM'S IODINE, ALCOHOL SOLUTION
Synonyms	Gram's Iodine, Alcoholic Solution / Iodine, Potassium Iodide Solution

Section 2 Hazards Identification

Signal word: DANGER**Pictograms:** GHS02 / GHS07 / GHS09**Target organs:** Eyes, Central nervous system, Liver, Kidneys, Thyroid**GHS Classification:**

Flammable liquid (Category 2)
Acute toxicity, oral (Category 5)
Acute toxicity, inhalation (Category 5)
Skin irritation (Category 2)
Eye irritation (Category 2B)
STOT-SE (Category 3)
Aquatic toxicity, acute (Category 1)

GHS Label information: Hazard statement:

H225: Highly flammable liquid and vapour.
H303: May be harmful if swallowed.
H333: May be harmful if inhaled.
H315: Causes skin irritation.
H319: Causes serious eye irritation.
H336: May cause drowsiness or dizziness.
H400: Very toxic to aquatic life.

Hazards not otherwise classified:

Health hazards not otherwise classified (HHNOC) - Not Known
Physical hazards not otherwise classified (PHNOC) - Not Known

Precautionary statement:

P210: Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P240: Ground/bond container and receiving equipment.
P241: Use explosion-proof electrical/ventilating/lighting equipment.
P242: Use only non-sparking tools.
P243: Take precautionary measures against static discharge.
P260: Do not breathe mist/vapours/spray.
P264: Wash hands thoroughly after handling.
P271: Use only outdoors or in a well-ventilated area.
P273: Avoid release to the environment.
P280: Wear protective gloves/protective clothing/eye protection/face protection.
P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P312: Call a POISON CENTER or doctor if you feel unwell.
P332+P313: If skin irritation occurs: Get medical attention.
P337+P313: If eye irritation persists: Get medical attention.
P362+P364: Take off contaminated clothing and wash it before reuse.
P391: Collect spillage.
P403+P233: Store in a well-ventilated place. Keep container tightly closed.
P501: Dispose of contents/container to a licensed chemical disposal agency in accordance with local/regional/national regulations.

Section 3 Composition / Information on Ingredients

Chemical Name	CAS #	%	EINECS
Ethyl alcohol, denatured*	64-17-5	65.55%	200-578-6
Water	7732-18-5	31.22%	231-791-2
Potassium iodide	7681-11-0	1.95%	231-659-4
Iodine	7553-56-2	1.28%	231-442-4
*Denaturants:			
Isopropyl alcohol	67-63-0	--	200-661-7
Methanol	67-56-1	--	200-659-6
Methyl isobutyl ketone	108-10-1	--	203-550-1

Section 4 First Aid Measures

INGESTION: MAY BE HARMFUL IF SWALLOWED. Call physician or Poison Control Center immediately. Induce vomiting only if advised by appropriate medical personnel. Never give anything by mouth to an unconscious person.

INHALATION: MAY BE HARMFUL, IF INHALED. CAUSES RESPIRATORY TRACT IRRITATION. Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

EYE CONTACT: CAUSES SERIOUS EYE IRRITATION. Check for and remove contact lenses. Flush thoroughly with water for at least 15 minutes, lifting upper and lower eyelids occasionally. Get immediate medical attention.

SKIN ABSORPTION: MAY BE HARMFUL IF ABSORBED THROUGH SKIN. CAUSES SKIN IRRITATION. Remove contaminated clothing. Flush thoroughly with mild soap and water. If irritation occurs, get medical attention.

Section 5 Fire Fighting Measures

Suitable Extinguishing Media: Dry chemical, CO₂, water spray or alcohol-resistant foam.

Protective Actions for Fire-fighters: In fire conditions, wear a NIOSH/MSHA-approved self-contained breathing apparatus and full protective gear. Use water spray to keep fire-exposed containers cool.

Specific Hazards: During a fire, irritating and highly toxic gases may be generated by thermal decomposition or combustion. Vapors formed from this product are heavier than air and may travel along the ground to a distant source of ignition and flash back instantly. Flame may not be visible in daylight.

Section 6 Accidental Release Measures

Personal Precautions: Evacuate personnel to safe area. Use proper personal protective equipment as indicated in Section 8. Provide adequate ventilation.

Environmental Precautions: Avoid runoff into storm sewers and ditches which lead to waterways.

Containment and Cleanup: Remove all sources of ignition. Absorb with inert dry material, sweep or vacuum up and place in a suitable container for proper disposal. Wash spill area with soap and water.

Precautions for Safe Handling: Read label on container before using. Do not wear contact lenses when working with chemicals. Keep out of reach of children. Avoid contact with eyes, skin and clothing. Do not inhale vapors, spray or mist. Use with adequate ventilation. Avoid ingestion. Wash thoroughly after handling. Remove and wash clothing before reuse.

Conditions for Safe Storage: Store in a cool, well-ventilated area away from incompatible substances. Keep away from ignition sources.

Section 8 Exposure Controls / Personal Protection

Exposure Limits:	Chemical Name	ACGIH (TLV)	OSHA (PEL)	NIOSH (REL)
	Ethanol	STEL: 1000 ppm / 1880 mg/m ³ (A3)	TWA: 1000 ppm / 1900 mg/m ³	TWA: 1000 ppm / 1900 mg/m ³

Engineering controls: Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower and fire extinguishing material. Personnel should wear safety glasses, goggles, or faceshield, lab coat or apron, appropriate protective gloves. Use adequate ventilation to keep airborne concentrations low.

Respiratory protection: None should be needed in normal laboratory handling at room temperatures. If misty conditions prevail, work in fume hood or wear a NIOSH/MSHA-approved respirator.

Section 9 Physical & Chemical Properties

Appearance: Liquid. Deep, amber colored	Evaporation rate (Ether = 1): >1	Partition coefficient: (n-octanol / water): Low Pow: -.32*
Odor: Mild characteristic odor.	Flammability (solid/gas): Data not available.	Auto-ignition temperature: 383°C (721°F)*
Odor threshold: Data not available.	Explosion limits: Lower / Upper: 3.3% / 19.0%*	Decomposition temperature: Data not available.
pH: Data not available.	Vapor pressure (mm Hg): Ca 50 @ 20°C*	Viscosity: Data not available.
Melting / Freezing point: -114°C (-173°F)*	Vapor density (Air = 1): Ca 1.5*	Molecular formula: Mixture
Boiling point: 74-80°C (165.2-176°F)*	Relative density (Specific gravity): 0.7919-0.7955°C @ 60/60°F*	Molecular weight: Mixture
Flash point: 21°C (70°F) TCC [70% ethanol]	Solubility(ies): Soluble in water.	*200 Proof Ethanol

Section 10 Stability & Reactivity

Chemical stability: Stable

Hazardous polymerization: Will not occur.

Conditions to avoid: Excessive temperatures, heat, sparks, open flame and other sources of ignition. Protect from light and air.

Incompatible materials: Strong oxidizers, inorganic acids and halogens. Contact of gaseous ammonia or its solutions with Iodine should be avoided to prevent the formation of the explosive "nitrogen iodide". May be corrosive to most metals.

Hazardous decomposition products: Carbon oxides and corrosive fumes of iodine.

Section 11 Toxicological Information

Acute toxicity: Ethanol: Oral-rat LD50: 7060 mg/kg ; Inhalation-rat LC50: 124.7 mg/l/4hours, Iodine: Oral-rat LD50: 14,000 mg/kg, Potassium iodide: Oral-rat LD50: 4800 mg/kg

Skin corrosion/irritation: Skin-rabbit - Slight irritant.

Serious eye damage/irritation: Eyes-rabbit - Severe irritant.

Respiratory or skin sensitization: Data not available

Germ cell mutagenicity: Data not available

Carcinogenicity: Data not available

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

IARC classified: Group 3: Not classifiable as to its carcinogenicity to humans. [Isopropanol]

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

CA Prop 65: ⚠️ WARNING! : This product can expose you to chemicals including Methanol and Methyl isobutyl ketone, which are known to the State of California to cause cancer and birth defects or other reproductive harm.

Reproductive toxicity: Data not available

STOT-single exposure: The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects.

STOT-repeated exposure: Data not available

Aspiration hazard: Data not available

Potential health effects:

Inhalation: Inhalation may cause dizziness, drowsiness, nausea, vomiting, inability to concentrate and irritation of the throat.

Ingestion: Ingestion causes dizziness, drowsiness, decreased reaction, euphoria, nausea, vomiting, staggering gait and coma.

Skin: Contact with skin causes irritation defatting on prolonged contact.

Eyes: Contact with eyes may cause blindness.

Signs and symptoms of exposure: See Potential health effects above.

Additional information: RTECS #: KQ6300000 [Ethanol]

Section 12 Ecological Information

Toxicity to fish: Oncorhynchus mykiss (fish, fresh water), LC50 = 11,200 mg/l/24 hours [Ethanol]

Toxicity to daphnia and other aquatic invertebrates: Daphnia magna (Crustacia), EC50 = 10,800 mg/l/24 hours [Ethanol, 99.8% pure]

Toxicity to algae: Chlorella pyrenoidosa (Algae), EC50 = 9,310 mg/l/growth rate [Ethanol, absolute]

Persistence and degradability: No data available

Bioaccumulative potential: No data available

Mobility in soil: No data available

PBT and vPvB assessment: No data available

Other adverse effects: Very toxic to aquatic life.

Section 13 Disposal Considerations

These disposal guidelines are intended for the disposal of catalog-size quantities only. Federal regulations may apply to empty container. State and/or local regulations may be different. Dispose of in accordance with all local, state and federal regulations or contract with a licensed chemical disposal agency.

Section 14 Transport Information (US DOT / CANADA TDG)

UN/NA number: UN1170

Shipping name: Ethanol solution

Hazard class: 3

Packing group: II

Reportable Quantity: 5,000 lbs (2270 kg)

Marine pollutant: No

Exceptions: Limited quantity equal to or less than 1 L

2016 ERG Guide # 127

Section 15 Regulatory Information

A chemical is considered to be listed if the CAS number for the anhydrous form is on the Inventory list.

Component	TSCA	CERLCA (RQ)	RCRA code	DSL	NDSL	CA Prop 65
Ethanol	Listed	Not listed	D001	Listed	Not listed	⚠️ WARNING -Cancer and Reproductive Harm - www.P65Warnings.ca.gov.
Methanol	Listed	5,000 lbs.	U154	Listed	Not listed	
Isopropanol	Listed	Not listed	Not listed	Listed	Not listed	

Section 16 Other Information

The information contained herein is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determinations of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. NTP: National Toxicology Program, IARC: International Agency for Research on Cancer, OSHA: Occupational Safety and Health Administration, STOT: Specific Target Organ Toxicity, SE: Single Exposure, RE: Repeated Exposure, ERG: Emergency Response Guidebook.

Section 1 L'identification de produit chimique et de compagnie

Page F1 of F2



5100 West Henrietta Rd
PO Box 92912
Rochester, NY 14692-9012
Tel: (800) 962-2660

Boreal Science
399 Vansickle Road
St. Catharines, Ontario
L2S 3T4 Canada
Tel: (800) 387-9393

**CHEMTREC 24 Numéros De Téléphone De
Secours D'Heure (800) 424-9300**
Pour l'usage industriel et de laboratoire seulement.
Pas pour l'usage de drogue, de nourriture ou de ménage.

Produit	GRAM'S IODE, SOLUTION D'ALCOOL
----------------	---------------------------------------

Synonymes	Gram's iode, une solution alcoolique / Iode et d'iode de potassium solution
------------------	---

Section 2 Identification De Risques

Mention d'avertissement: DANGER

Pictogrammes: GHS02 / GHS07 / GHS09

Les organes cibles: Les yeux, le système nerveux central, le foie et les reins, thyroïde



Classification par le GHS:

Flammable liquid (Catégorie 2)
Acute toxicity, oral (Catégorie 5)
Acute toxicity, inhalation (Catégorie 5)
Skin irritation (Catégorie 2)
Eye irritation (Catégorie 2B)
STOT-SE (Catégorie 3)
Aquatic toxicity, acute (Catégorie 1)

Renseignements sur l'étiquette GHS: Mention de danger:

H225: Liquide et vapeurs très inflammables.
H303: Peut être nocif en cas d'ingestion.
H333: Peut être nocif par inhalation.
H315: Provoque une irritation cutanée.
H319: Provoque une sévère irritation des yeux.
H336: Peut provoquer somnolence ou des vertiges.
H400: Très toxique pour les organismes aquatiques.

Dangers non classés autrement:

Dangers pour la santé non classés ailleurs (HHNOC) - pas connu
Dangers physiques non classés autrement (PHNOC) - pas connu

Section 3 Composition / Information Sur Des Ingrédients

Nommé Chimique	# CAS	%	EINECS
Alcool éthylique, dénaturé*	64-17-5	65.55%	200-578-6
L'eau	7732-18-5	31.22%	231-791-2
Iodure de potassium	7681-11-0	1.95%	231-659-4
Iode	7553-56-2	1.28%	231-442-4
*Dénaturants:			
Alcool isopropylique	67-63-0	--	200-661-7
Méthanol	67-56-1	--	200-659-6
Cetone isobutylique méthylique	108-10-1	--	203-550-1

Section 4 Mesures De Premiers Soins

INGESTION: PEUT ÊTRE NOCIF EN CAS D'INGESTION. Appeler un médecin ou un centre antipoison immédiatement. Provoquer le vomissement seulement si elle est informée par le personnel compétent médicaux. Ne jamais rien donner par la bouche à une personne inconsciente.

INHALATION: PEUT ÊTRE NOCIF EN CAS D'INHALATION. IRRITE LES VOIES RESPIRATOIRES. Sortir au grand air. Si elle ne respire pas, pratiquer la respiration artificielle. Si la respiration est difficile, donner de l'oxygène. Obtenir des soins médicaux.

CONTACT AVEC LES YEUX: PROVOQUE UNE SÉVÈRE IRRITATION DES YEUX. Vérifier et enlever les lentilles de contact. Rincer abondamment à l'eau pendant au moins 15 minutes, en soulevant les paupières inférieures et supérieures de temps en temps. Obtenez une attention médicale immédiate.

ABSORPTION PAR LA PEAU: PEUT ÊTRE NOCIF EN CAS D'ABSORPTION PAR LA PEAU. CAUSER UNE IRRITATION DE LA PEAU. Enlever les vêtements contaminés. Rincer soigneusement avec du savon doux et d'eau. En cas d'irritation, consulter un médecin.

Section 5 Mesures De Lutte Contre l'Incendie

Moyens d'extinction: Produit chimique sec, CO₂, eau pulvérisée ou de la mousse résistant à l'alcool.

Actions de protection pour les sapeurs-pompiers: En cas d'incendie, porter un appareil respiratoire NIOSH / MSHA approuvé autonome et un équipement complet de protection. Utiliser un jet d'eau pour maintenir incendie refroidir les conteneurs exposés.

Dangers spécifiques: En cas d'incendie, des gaz irritants et très toxiques peuvent être générés par la décomposition thermique ou la combustion. Les vapeurs formées de ce produit sont plus lourdes que l'air et peuvent voyager le long de la terre à une source d'ignition et voyagez dos immédiatement. La flamme peut ne pas être évidente en jour.

Section 6 Mesures De Déchargement Accidentel

Précautions personnelles: Évacuer le personnel vers la zone sûre. Utiliser un équipement de protection personnelle comme indiqué dans la Section 8. Assurer une ventilation adéquate.

Précautions environnementales: Éviter tout ruissellement vers les égouts pluviaux et les fossés qui aboutissent aux voies navigables.

Confinement et de nettoyage: Absorbent avec le matériel sec inerte, balayez ou nettoyez à l'aspirateur vers le haut et placez dans un récipient approprié pour la disposition appropriée. Laver la zone de déversement avec du savon et de l'eau.

Précautions pour la manutention en toute sécurité: Lire l'étiquette sur le contenant avant d'utiliser. Ne pas porter de lentilles cornéennes lorsque vous travaillez avec des produits chimiques. Tenir hors de portée des enfants. Éviter tout contact avec les yeux, la peau et les vêtements. Ne pas inhaler les vapeurs, les embruns ou le brouillard. Utiliser avec une ventilation adéquate. Éviter l'ingestion. Bien se laver après la manipulation. Retirer et laver les vêtements avant de les réutiliser.

Conditions de stockage: Stocker dans un endroit frais et bien aéré, loin des substances incompatibles. Substance loin des sources d'allumage.

Section 8 Commandes D'Exposition / Protection Personnelle

Limites d'exposition:	Nommé Chimique	ACGIH (TLV)	OSHA (PEL)	NIOSH (REL)
	Éthanol	STEL: 1000 ppm / 1880 mg/m ³ (A3)	TWA: 1000 ppm / 1900 mg/m ³	TWA: 1000 ppm / 1900 mg/m ³

Contrôles d'ingénierie: Les installations d'entreposage ou d'utilisation de ce matériel doit être équipé d'une douche oculaire et une douche de sécurité et le matériel d'extinction d'incendie. Le personnel doit porter des lunettes de sécurité, des lunettes, ou un écran facial, une blouse de laboratoire ou tablier, des gants protecteurs appropriés. Utiliser une ventilation adéquate pour maintenir les concentrations atmosphériques faible.

Protection respiratoire: Aucun ne devrait être nécessaire dans le laboratoire normal manipulant aux températures ambiantes. En cas de les conditions brumeux, travaillez dans le capot de vapeur ou portez un respirateur de NIOSH/MSHA-approved.

Section 9 Propriétés Physiques Et Chimiques

Apparence: Liquide. Profonde, de couleur ambre	Taux d'évaporation (Éther = 1): >1	Coefficient de partage: (n-octanol / eau): Low Pow: -32*
Odeur: Odeur caractéristique douce.	Inflammabilité (solide / gaz): Données non disponibles.	Auto-inflammation: 383°C (721°F)*
Seuil de l'odeur: Données non disponibles.	Limites d'explosivité: Bas / Max: 3,3% / 19,0%*	Température de décomposition: Données non disponibles.
pH: Données non disponibles.	Pression de vapeur (mm Hg): Ca 50 @ 20°C*	Viscosité: Données non disponibles.
Point de fusion / congélation: -114°C (-173°F)*	Densité de vapeur (Air = 1): Ca 1.5*	Formule moléculaire: Mélange
Point d'ébullition: 74-80°C (165.2-176°F)*	Densité relative (gravité spécifique): 0.7919-0.7955°C @ 60/60°F*	Poids moléculaire: Mélange
Point d'éclair: 21°C (70°F) [70% éthanol]	Solubilité (s): Soluble dans l'eau.	*200 Proof Éthanol

Section 10 Stabilité Et Réactivité

Stabilité chimique: Stable

Polymérisation dangereuse: N'aura pas lieu.

Conditions à éviter: Les températures excessives, la chaleur, étincelles, flamme nue et d'autres sources d'allumage. Protéger de la lumière et de l'air.

Matières incompatibles: Comburentes fortes, acides inorganiques et l'halogènes. Le contact de l'ammoniac gazeux ou de ses solutions avec de l'iode doit être évitée pour empêcher la formation de l'explosif "iodure d'azote". Peut être corrosif pour la plupart des métaux.

Produits dangereux de décomposition: Oxydes de carbones et vapeurs corrosives de l'iode.

Section 11 L'Information Toxicologique

Toxicité aiguë: Ethanol: Oral-rat LD50: 7060 mg/kg ; Inhalation-rat LC50: 124.7 mg/l/4hours, Iodine: Oral-rat LD50: 14,000 mg/kg, Potassium iodide: Oral-rat LD50: 4800 mg/kg

La corrosion de la peau et l'irritation: Peau de lapin - Légèrement irritant.

Des lésions oculaires graves / irritation: Yeux-lapin - Irritant sévère.

Respiratoire ou sensibilisation de la peau: Données non disponibles

Mutagenicité des cellules germinales: Données non disponibles

Cancérogène: Données non disponibles

NTP: Aucun composant de ce produit présent à des niveaux supérieurs ou égaux à 0,1% n'a été identifié comme cancérogène reconnu ou présumé par NTP.

IARC classés: Group 3: L'agent est inclassable quant à sa cancérogénicité pour l'homme. [Isopropanol]

OSHA: Aucun composant de ce produit présent à des niveaux supérieurs ou égaux à 0,1% n'a été identifié comme cancérogène ni comme cancérogène possible par OSHA.

Reproductive toxicity: Données non disponibles

STOT-exposition unique: La substance ou le mélange est classé comme toxique pour certains organes cibles, exposition unique, catégorie 3 avec des effets narcotiques.

STOT-une exposition répétée: Données non disponibles

Risque d'aspiration: Données non disponibles

Effets d'une surexposition:

Inhalation: L'inhalation peut causer des étourdissements, somnolence, nausées, vomissements, incapacité à se concentrer et l'irritation de la gorge.

Ingestion: L'ingestion provoque des étourdissements, la somnolence, la réaction a diminué, l'euphorie, des nausées, des vomissements, démarche titubante et le coma.

Peau: Contact avec la peau cause une irritation délipidation au contact prolongé.

Yeux: Contact avec les yeux peut causer la cécité.

Les signes et les symptômes de l'exposition: Voir les effets sanitaires potentiels ci-dessus.

Informations complémentaires: RTECS #: KQ6300000 [Éthanol]

Section 12 L'Information Écologique

Toxicité pour les poissons: Oncorhynchus mykiss (fish, fresh water), LC50 = 11,200 mg/l/24 hours [Éthanol]

Toxicité pour les daphnies et autres invertébrés aquatiques: Daphnia magna (Crustacia), EC50 = 10,800 mg/l/24 hours [Éthanol, 99.8% pure]

Toxicité pour les algues: Chlorella pyrenoidosa (Algae), EC50 = 9,310 mg/l/growth rate [Éthanol, absolute]

Persistance et dégradabilité: Pas de données disponible

Potentiel de bioaccumulation: Pas de données disponible

Mobilité dans le sol: Pas de données disponibles

Évaluation PBT et vPvB: Pas de données disponibles

Autres effets indésirables: Très toxique pour les organismes aquatiques.

Section 13 Considérations De Disposition

Ces lignes directrices sont destinées à l'élimination de la disposition d'un catalogue de taille seules les quantités. Les règlements fédéraux peuvent s'appliquer aux contenants vides. Des réglementations nationales et / ou local peut être différent. Éliminer conformément à toutes les réglementations locales, provinciales et fédérales ou d'un contrat avec une agence élimination des produits chimiques sous licence.

Section 14 L'Information De Transport (US DOT / CANADA TMD)

Numéro UN / NA: UN1170 **Nom d'expédition:** Solution d'éthanol

Classe de danger: 3

Groupe d'emballage: II

Quantité à déclarer: 5,000 lbs. (2270 kg)

Polluant marin: No

Exceptions: Quantité limitée égale à ou moins de 1 L

2016 ERG Guide #: 127

Section 15 L'Information De Normalisation

Un produit chimique est considéré comme inscrit si le numéro CAS pour la forme anhydre est sur la liste d'inventaire.

Composant	TSCA	CERLCA (RQ)	RCRA code	DSL	NDSL
Éthanol	Listed	Not listed	D001	Listed	Not listed
Méthanol	Listed	5,000 lbs.	U154	Listed	Not listed
Isopropanol	Listed	Not listed	Not listed	Listed	Not listed

Section 16 L'autre Information

Les informations contenues dans ce document sont fournis sans garantie d'aucune sorte. Les employeurs devraient considérer cette information seulement comme complément à d'autres informations recueillies par eux et doivent prendre des décisions indépendantes de la pertinence et l'exhaustivité de l'information de toutes les sources afin d'assurer une utilisation correcte de ces matériaux et de la sécurité et la santé des employés. NTP: National Toxicology Program, IARC: International Agency for Research on Cancer, OSHA: Occupational Safety and Health Administration, STOT: Specific Target Organ Toxicity, SE: Single Exposure, RE: Repeated Exposure, ERG: Emergency Response Guidebook.