

MATERIAL SAFETY DATA SHEET

KRYLON PRODUCTS GROUP
THE SPECIALTY DIVISION
DIV. OF THE SHERWIN-WILLIAMS COMPANY
31500 SOLON ROAD
SOLON, OH 44139

EMERGENCY TELEPHONE NO.
(216) 292-7400
INFORMATION TELEPHONE NO.
(800) 832-2541 - HARDWARE

DATE OF PREPARATION
1 - Aug - 94

©1994, The Sherwin-Williams Co.

Ace Hardware
(Spray Paints) various

QDL/CW2

ColorWorks® from KRYLON Quick Dry Lacquers - 2

SECTION II CAS No. HAZARDOUS INGREDIENT (percent by weight)		ACGIH TLV <STEL>	OSHA PEL <STEL>	Unit	Vapor Pressure (mm Hg)	CWA-1150 Gloss Black	CWA-1151 Flat Black	CWA-1152 Gloss White	CWA-1153 Flat White	CWA-1154 Almond	CWA-1155 Ocean Blue	CWA-1156 Sunshine Yellow	CWA-1157 Walnut	CWA-1158 Red Ribbon	CWA-1159 Clear Gloss	CWA-1160 Clear Satin	CWA-1161 Red Oxide Primer	
74-98-6	Propane (propellant)	1000		PPM	760.0	13	13	13	13	13	13	13	13	13	16	16	12	
75-28-5	2-Methylpropane (propellant)	Not Established			760.0	7	7	7	7	7	7	7	7	7			16	
14742-89-8	V. M. & P. Naphtha	300	300 <400>	PPM	12.0										2			
14742-47-8	Mineral Spirits	100	100	PPM	2.0											2		
108-88-3	§ Toluene	50	100 <150>	PPM (Skin)	22.0											2		
100-41-4	§ Ethylbenzene	100 <125>	100 <125>	PPM	7.1	2	2	2	2	2	2	2	2	2	1	2	17	
1330-20-7	§ Xylene	100 <150>	100 <150>	PPM	5.9	10	13	11	13	9	9	9	11	10	6	8		
67-63-0	§ 2-Propanol	400 <500>	400 <500>	PPM	33.0										2	2	1	
71-36-3	§ 1-Butanol	C 50	C 50	PPM	5.5			2			2	1						
67-64-1	§ Acetone	750 <1000>	750 <1000>	PPM	180.0	35	34	35	35	34	35	35	35	34	43	21	32	
78-93-3	§ Methyl Ethyl Ketone	200 <300>	200 <300>	PPM	70.0	12	10	4	4	8	7	8	8	8	4	22		
108-10-1	§ Methyl Isobutyl Ketone	50 <75>	50 <75>	PPM	16.0	1	1			2	3	3	1	3	4	4		
763-69-9	Ethyl 3-Ethoxypropionate	Not Established			1.1										6		2	
123-86-4	n-Butyl Acetate	150 <200>	150 <200>	PPM	10.0										2			
110-19-0	Isobutyl Acetate	150	150	PPM	12.5												5	
628-63-7	Amyl Acetate	100	100	PPM	4.0										4	4		
108-21-4	§ Isopropyl Acetate	250 <310>	250 <310>	PPM	47.5										4	5		
108-65-8	1-Methoxy-2-Propanol Acetate	Not Established			1.8	8	7	7	7	7	7	8	7	7				
231-67-4	Amorphous Silica	10	6	Mg/M3	as Dust				1									
171-34-1	Calcium Carbonate	10	15[5]	Mg/M3	as Dust [Resp Fraction]												1	
1463-67-7	Titanium Dioxide	10	10[5]	Mg/M3	as Dust [Resp Fraction]			7	7	6		2						
133-86-4	Carbon Black	3.5	3.5	Mg/M3			1											
1307-96-6	Talc	10	10[5]	Mg/M3	as Dust [Resp Fraction]												9	
VOC as a percent by weight per BAAQMD Rule 49						88	89	81	82	82	86	85	86	85	92	86	85	
HMIS® Ratings (Health - Flammability - Reactivity)						2-4-0	2-4-0	2-4-0	2-4-0	2-4-0	2-4-0	2-4-0	2-4-0	2-4-0	2-4-0	2-4-0	2-4-0	2-4-0

§ Ingredient subject to the reporting requirements of the Superfund Amendments and Reauthorization Act (SARA) Section 313, 40 CFR 372.65 C

OCT-05-1995 14:21 FROM FULFILLMENT CENTER INC. TO 17172881068 P.02