

Smith Art

## DAL-WORTH PAINT MFG CO -- 752 DURA-KOTE ACRYLIC H P -- 8010-00F039479

## = ===== Product Identification =====

Product ID:752 DURA-KOTE <sup>Various</sup> ACRYLIC H P <sub>Paints</sub>  
 MSDS Date:09/28/1992  
 FSC:8010  
 NIIN:00F039479  
 MSDS Number: BWXBW  
 === Responsible Party ===  
 Company Name:DAL-WORTH PAINT MFG CO  
 Address:733 DALWORTH DR  
 Box:850173  
 City:MESQUITE  
 State:TX  
 ZIP:75149-0173  
 Country:US  
 Info Phone Num:214-285-6346  
 Emergency Phone Num:214-285-6346  
 CAGE:DALWO

=== Contractor Identification ===  
 Company Name:DAL-WORTH PAINT MFG CO  
 Address:733 DALWORTH DR  
 Box:173  
 City:MESQUITE  
 State:TX  
 ZIP:75149-0173  
 Country:US  
 Phone:214-285-6346  
 E:DALWO

## ===== Composition/Information on Ingredients =====

Ingred Name:TITANIUM DIOXIDE, TIO2 (SUSPECTED ANIMAL CARCINOGEN, IARC  
 GROUP 3) \*95-1\*  
 CAS:13463-67-7  
 RTECS #:XR2275000  
 Fraction by Wt: 20.5%  
 OSHA PEL:10 MG/CUM  
 ACGIH TLV:10 MG/CUM (DUST)

Ingred Name:CALCIUM CARBONATE, DOMOLITE, LIMESTONE, WHITING  
 CAS:1317-65-3  
 RTECS #:EV9580000  
 Fraction by Wt: 15.7%  
 OSHA PEL:5 MG/CUM  
 ACGIH TLV:10 MG/CUM (DUST)

Ingred Name:SILICON DIOXIDE, CRYSTALLINE QUARTZ, SAND (ANIMAL CARC,  
 SUSPECTED HUMAN CARC IARC-GROUP 2A; SUSPECTED CARC NTP) \*95-1\*  
 CAS:14808-60-7  
 RTECS #:VV7330000  
 Fraction by Wt: 0.3%  
 Other REC Limits:0.05 MG/CUM NIOSH  
 OSHA PEL:0.1 MG/CUM RESP DUST  
 ACGIH TLV:0.1 MG/CUM RESP DUST

Ingred Name:TALC (POWDER), (ASBESTOS FREE), TALCUM; HYDROUS MAGNESIUM  
 SILICATE

CAS:14807-96-6  
 RTECS #:WW2710000  
 Fraction by Wt: 20.3%  
 C O PEL:2 MG/CUM  
 ACGIH TLV:2 MG/CUM (RESP DUST)

Ingred Name:AMORPHOUS SILICA, AMORPHOUS-DIATOMACEOUS EARTH  
 CAS:61790-53-2  
 RTECS #:HL8600000  
 Fraction by Wt: 2.4%  
 Other REC Limits:20 MCCPF (MSHA)  
 OSHA PEL:5 MG/CUM  
 ACGIH TLV:10 MG/CUM DUST

Ingred Name:RED IRON OXIDE/IRON (III) OXIDE/FERRIC OXIDE/YELLOW FERRIC  
 OXIDE/YELLOW IRON OXIDE/IRON OXIDE PIGMENT  
 CAS:1309-37-1  
 RTECS #:NO7400000  
 Fraction by Wt: 8.3%  
 OSHA PEL:10 MG/CUM  
 ACGIH TLV:5 MG/CUM (FE)

Ingred Name:CLAY (KAOLIN), ALUMINUM SILICATE  
 CAS:1332-58-7  
 RTECS #:GF1670500  
 Fraction by Wt: 6.7%  
 OSHA PEL:10 MG/CUM  
 ACGIH TLV:10 MG/CUM TOTAL DUST

Ingred Name:YELLOW OXIDE, YELLOW IRON OXIDE \*95-1\*  
 CAS:51274-00-1  
 Fraction by Wt: 1.3%  
 OSHA PEL:10 MG/CUM  
 ACGIH TLV:10 MG/CUM

Ingred Name:COLUMBIA CARBON, CARBON BLACK, LAMPBLACK, BLACK PEARLS  
 (IARC GROUP 3) - \*95-1\*  
 CAS:1333-86-4  
 RTECS #:FF5800000  
 Fraction by Wt: 1.3%  
 Other REC Limits:3.5 MG/CUM (NIOSH)  
 OSHA PEL:3.5 MG/CUM  
 ACGIH TLV:3.5 MG/CUM

=====  
 Hazards Identification  
 =====

Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES  
 Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:NO  
 Health Hazards Acute and Chronic:INHALATION: NOSE & THROAT IRRITATION.  
 MAY CAUSE LUNG IRRITATION. SKIN/EYES: PRIMARY IRRITATION.  
 INGESTION: LARGE AMOUNTS INGESTED COULD CAUSE SERIOUS INJURY.  
 OVEREXPOSURE INHALATION OF SANDING DUST MAY CAUSE LUNG DAMAGE.  
 Explanation of Carcinogenicity:SEE INGREDIENTS  
 Effects of Overexposure:IRRITATION

=====  
 First Aid Measures  
 =====

First Aid:INHALATION: REMOVE TO FRESH AIR. EYES: FLUSH THOROUGHLY  
 W/WATER. SKIN: WASH W/SOAP & WATER. INGESTION: DRINK 1-2 GLASSES OF  
 WATER TO DILUTE. DON'T INDUCE VOMITING. OBTAIN MEDICAL ATTENTION IN

ALL CASE S.

===== Fire Fighting Measures =====

Flash Point Method:PMCC

Flash Point:>250F

Extinguishing Media:FOAM, CO2, DRY CHEMICAL, WATER FOG

Fire Fighting Procedures:COOL EXPOSED CONTAINERS W/WATER. USE SELF  
CONTAINED BREATHING APPARATUS.

Unusual Fire/Explosion Hazard:CLOSED CONTAINERS MAY BURST IF EXPOSED TO  
EXTREME HEAT/FIRE. TOXIC GASES MAY FORM WHEN PRODUCT BURNS.

===== Accidental Release Measures =====

Spill Release Procedures:FLUSH W/WATER. ABSORB W/SAWDUST/RAGS.

===== Handling and Storage =====

Handling and Storage Precautions:DON'T THROW/DROP CONTAINERS. CLOSE  
CONTAINERS AFTER EACH USE. KEEP OUT OF REACH OF CHILDREN. DON'T  
TAKE INTERNALLY.

Other Precautions:AVOID CONTACT W/EYES & PROLONGED CONTACT  
W/SKIN/BREATHING OF SPRAY MIST/SANDING DUST.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH APPROVED RESPIRATOR FOR PROTECTION  
AGAINST SPRAY MIST & SANDING DUST IN RESTRICTED/CONFINED AREAS.

Ventilation:ADEQUATE TO MAINTAIN WORKING ATMOSPHERE 1

Evaporation Rate & Reference:SLOWER THAN ETHER

Percent Volatiles by Volume:(SUPP)

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

Stability Condition to Avoid:ELEVATED TEMPERATURES

Hazardous Decomposition Products:CO2, CO

===== Disposal Considerations =====

Waste Disposal Methods:DON'T INCINERATE SEALED CONTAINERS. DISPOSE OF  
IN ACCORDANCE W/LOCAL, STATE & FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.