JOHNSON MANUFACTURING COMPANY Material Safety Data Sheet

to comply with 29 CFR 1910.1200, OSHA's Hazard Communication Standard

Johnson's Soldering Fluid, 01-00

Section I:

Johnson Manufacturing Company 114 Lost Grove Road Princeton IA 52768

Emergency Telephone (563)-289-5123 CHEMTREC after hours 1-(800)-424-9300 Revised 1/1/2006

Section II: Hazardous Ingredients/Identity information

Hazardous Component CAS	# OSHA TWA	ACGIH TWA	Other limits		
+ Zinc Chloride 7646-85-	7 1mg/M3	1mg/M3	NE	39	96
Ammonium Chloride 12125	-02-9 10mg/M3	10mg/M3	NE		
As Zinc Ammonium Chloride					

Only those ingredients listed in this section have been determined to be hazardous as defined in 29CFR 1910.1200. An ingredient marked with an asterisk(*) is also listed in 29CFR 1910.1200(D) #4 as a known or suspected cancer hazard.

+ denotes a chemical regulated as toxic by the Environmental Protection Agency (EPA) as outlined in 40CFR Part 372 (section 313)

Section III: Physical/Chemical Characteristics

Boiling Point: 230 F Specific Gravity: 1.403
Vapor Pressure (mm Hg): NE Melting Point: NE
Vapor Density: NE Evaporation Rate
Solubility in water: 100 (butyl acetate=1): < 1
Appearance and odor: clear to yellow liquid, wintergreen odor

Section IV: Fire and Explosion Hazard Data

Section V: Reactivity Data

Section VI: Health Hazard Data:

Routes of entry: Inhalation? yes Skin? no Ingestion? yes

Health Hazards (acute and chronic) Contact with material or fumes may cause skin, eye and respiratory tract irritation or burns. Severe inhalation can cause pulmonary edema, which may not manifest for several hours after exposure. Ingestion may result in irritation or burning of the digestive tract. Gross inhalation or ingestion can result in death. LD50 (ZnCl2)(rat)=350 mg/kg.

May be mutagenic in lab animals. May cause sensitization. Chronic exposures can result in permanent liver, kidney and respiratory system effects. Studies show that health risks vary by individual. Minimize exposure as a precaution.

Carcinogenicity: not determined NPT? no IARC Monographs? no

Signs and symptoms of exposure: Inhalation-Nose & throat irritation, headache, dizziness, difficulty breathing, coughing. Ingestion-nausea, vomiting, cramps. Skin-redness, burning, rash, dryness. Eye-redness, burning, tearing, blurred vision.

Medical conditions aggravated by exposure: Skin, kidney and respiratory conditions.

Emergency first aid procedures:

Skin: Flush with water immediately - Seek medical attention if necessary Eyes: Flush with water for 15 minutes - Seek medical attention

Ingestion: DO NOT induce vomiting, drink large amounts of water - seek medical

Inhalation: Remove to fresh air. Support respiration if required - Seek medical

attention. Never give anything by mouth to an unconscious person

Section VII: Precautions for Safe Handling and Use

attention.

Steps to be taken if material is released or spilled: Flush into a chemical sewer or soak up with a suitable absorbant.

Waste Disposal Method: dispose of in accordance with all local state and federal regulations

Other Precautions: Avoid skin and eye contact, inhalation and ingestion of fumes and material. Wash contaminated clothing before reuse.

Keep away from children. Do not reuse container.

Section VIII: Control Measures

Respiratory Protection (type): Acid type respirator for fumes and mist.

Ventilation: Local Exhaust preferred Special:NE

Mechanical OK Other:NE

Protective Gloves: plastic or rubber Eye Protection: Goggles or face shield

Other Protective Clothing or Equipment: as required to avoid contact.

Work/Hygenic Practices: Wash after use. Follow good industrial hygienic practices.

Section IX: Additional Information

```
DOT Classification: Non-Hazardous NFPA Classification (NFPA 325M,8<sup>th</sup> edition)(Health, Flammability, Reactivity): 2-0-0
```

This product contains components known to the state of California to cause cancer or reproductive harm

The information and recommendations contained within this publication have been compiled from sources believed to be reliable and to represent the best information available to JOHNSON MANUFACTURING at the time of issue. No warranty, guarantee, or representation is made by JOHNSON MANUFACTURING nor does JOHNSON MANUFACTURING assume any responsibility in connection therewithin; nor can it be assumed that all acceptable safety measures or other safety measures may not be required under particular or exceptional conditions or circumstances.

NE- not established NA = not applicable

Form 303.72 Rev.A

Back